

ARMSTRONG



Waste Water Pumping Systems

FILE NO:	14-1
DATE:	August 2010
SUPERSEDES:	14-1
DATE:	July 2007

The HOMA Partnership



HOMA Pumpen was founded in 1963. The company's engineering expertise is continually expanding and has progressively built upon the knowledge gained over a fifty year period when Herr Hoffmann, the founder, first started his enterprise in 1946 with the building of electric motors. Recognising the market potential he began to design and manufacture submersible motors and pumps.

Armstrong works in partnership with HOMA by offering this extensive range of waste water pumping systems.

► Drainage Pumps

Drainage or water supply applications e.g. house / contractors' drainage, construction sites, sumps and for water containing suspended sand, mud and gravel.

Spherical clearance up to 35mm.

Capacity up to 95 l/s.

1ph or 3ph models.

Vortex impeller. Head up to 72m.

Transportable or permanent installation.

Explosion-proof models available.



► Effluent and Waste Water Pumps

Series 'TP' compact cast iron pumps for effluent and waste water containing solids.

Spherical clearance up to 70mm.

Head up to 18.6m. Capacity up to 35 l/s.

1ph or 3ph models.

Single channel or vortex impeller.

Wet or dry well installation.

Explosion-proof models available.



Product overview

► Cutter Pumps

Barracuda cutter pumps for high head waste water and sewage pumping.

Hard metal cutter device at pump inlet.

Head up to 69m.

Transportable or permanent installation.

Explosion-proof models available.

Capacity up to 9 l/s.

1ph or 3ph models.



► Sewage and Waste Water Disposal Pumps

Series 'A' for sewage and waste water disposal, sewage pumping stations and treatment plants.

Spherical clearance up to 220mm.

Head up to 60m. Capacity up to 1250 l/s.

1ph or 3ph models.

Channel or vortex impeller.

Wet or dry well installation.

Explosion-proof models available.



► Sewage and Waste Water Disposal Units

For sewage and waste water disposal from sanitary installations below sewer levels. Tanks up to 1000 litre volume with one or two submersible pumps.

Spherical clearance up to 100mm.

Head up to 33m. Capacity up to 55 l/s.

1ph or 3ph models.

Closed single channel or vortex impellers.

Dry well installation.

Explosion-proof models available.



► Self-priming Centrifugal Pumps

Pumps for garden watering, water supply, tank emptying, emergency pumping etc.

Booster sets for automatic pressure water supply for garden watering and domestic water supply.

Head up to 63m. Capacity up to 1.6 l/s.

1ph models

Transportable or permanent installation.



Other Products in the Armstrong range include:

► Vertical In Line Pumps



► Packaged Solutions



► Fire Pump Systems



► Pressurisation Sets



► Booster Sets



► Heat Exchanger Units



Our policy is one of continuous improvement and we reserve the right to alter our dimensions and specifications without notice

Armstrong Integrated Limited
Wenlock Way
Manchester
United Kingdom, M12 5JL
T: +44 (0) 8444 145 145
F: +44 (0) 8444 145 146

S. A. Armstrong Limited
23 Bertrand Avenue
Toronto, Ontario
Canada, M1L 2P3
T: 001 416 755 2291
F: 001 416 759 9101

ARMSTRONG 