



EXCHANGER SIZE * - BAFFLE SPACING	DIMENSIONS											
	A		B		C		D		N1		N2	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
WX-184-2*-2	68 3/8	1737	33 1/2	851	20	508	52	1321	6	152	6	152
WX-185-2*-2	80 3/8	2042	45 1/2	1156	32	813	64	1626	6	152	6	152
WX-186-2*-2	92 3/8	2346	57 1/2	1461	44	1118	76	1930	6	152	6	152
WX-187-2*-2	104 3/8	2651	69 1/2	1765	56	1422	88	2235	6	152	6	152
WX-188-2*-2	116 3/8	2956	81 1/2	2070	68	1727	100	2540	6	152	6	152
WX-189-2*-2	128 3/8	3261	93 1/2	2375	80	2032	112	2845	6	152	6	152
WX-1810-2*-2	140 3/8	3566	105 1/2	2680	92	2337	124	3150	6	152	6	152
WX-1811-2*-2	152 3/8	3870	117 1/2	2985	104	2642	136	3454	6	152	6	152
WX-1812-2*-2	164 3/8	4175	129 1/2	3289	116	2946	148	3759	6	152	6	152
WX-1813-2*-2	176 3/8	4480	141 1/2	3594	128	3251	160	4064	6	152	6	152
WX-1814-2*-2	188 3/8	4785	153 1/2	3899	140	3556	172	4369	6	152	6	152
WX-1815-2*-2	200 3/8	5090	165 1/2	4204	152	3861	184	4674	6	152	6	152

NOZZLE SCHEDULE				
SERVICE	MARK	SHELL SIDE	MARK	TUBE SIDE
INLET	N1	AS PER TABLE	N5	8 (203) FLG
OUTLET	N2	AS PER TABLE	N6	8 (203) FLG
DRAIN	N3	1/2 (13) NPT		
VENT	N4	3/4 (19) NPT		

NOTES: 1. SUPPORTS SUPPLIED ONLY IF SPECIFIED ON ORDER.
 2. NOZZLE SIZES SHOWN ARE RECOMMENDED FOR MAXIMUM EXCHANGER LIFE.
 3. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.
 4. DRAWING IS NOT TO SCALE.
 5. ALL DIMN'S ±1/8 (3) UNLESS OTHERWISE SHOWN.

DESIGN CONDITIONS				
	SHELL		TUBES	
DESIGN PRESSURE	150 PSIG	1034 KPa	150 PSIG	1034 KPa
DESIGN TEMPERATURE	375 °F	191 °C	375 °F	191 °C
MIN. DESIGN METAL TEMP.	40 °F	4.4 °C	40 °F	4.4 °C
HYDRO. TEST PRESSURE	225 PSIG	1551 KPa	300 PSIG	2068 KPa
CONTENTS	WATER		WATER	

CUSTOMER:
 LOCATION:
 ENGINEER:
 ORDER No.:
 PROJECT/JOB:
 LOCATION:
 TAG: (QUOTE #)

TITLE	G.A. 150 LB. WX SERIES HEAT EXCHANGERS	A R M S T R O N G				NUMBER	WX-18-2P-2 (6)	REV.			
DATE:	12 / 01 / 94	BY:	D.C.R.	TEL :	(416) 755-2291	TEL :	(514) 421-2424	TEL :	(716) 693-8813	TEL :	(44) 120-657-9491