



EXCHANGER SIZE	DIMENSIONS								NOZZLE SCHEDULE		
	"A"		"B"		"C"		"D"		N1	INLET	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	N2	OUTLET	
THW-812-2-2	21 -1/2	546	12-1/8	289	15	381	-	-	N3	DRAIN	
THW-818-2-2	27 -1/2	699	18-1/8	441	21	533	-	-	COLLAR ASSEMBLY		
THW-824-2-2	33 -1/2	851	24-1/8	594	27	686	12-1/4	311	STANDARD		OVS. FOR STONE LINING
THW-830-2-2	39 -1/2	1003	30-1/8	746	33	838	18-1/4	464	"E"	8-5/8" (219)	10-3/4" (273)
THW-836-2-2	45 -1/2	1156	36-1/8	899	39	991	24-1/4	616	"F"	8" (203)	8-1/2" (216)
THW-842-2-2	51 -1/2	1308	42-1/8	1051	45	1143	30-1/4	768	DESIGN CONDITIONS		
THW-848-2-2	57 -1/2	1461	48-1/8	1203	51	1295	36-1/4	921	TUBES		
THW-854-2-2	63 -1/2	1613	54-1/8	1356	57	1448	42-1/4	1073	DESIGN PRESSURE	150 PSIG	1034 KPa
THW-860-2-2	69 -1/2	1765	60-1/8	1508	63	1600	48-1/4	1226	DESIGN TEMPERATURE	375 F	191 C
THW-866-2-2	75 -1/2	1918	66-1/8	1680	69	1753	54-1/4	1378	M.D.M.T.	35 F	1.7 C
THW-872-2-2	81 -1/2	2070	72-1/8	1832	75	1905	60-1/4	1530	HYD. TEST PRESSURE	300 PSIG	2068 KPa
THW-878-2-2	87 -1/2	2223	78-1/8	1984	81	2057	66-1/4	1683	NOTES:		
THW-884-2-2	93 -1/2	2375	84-1/8	2137	87	2210	72-1/4	1835	1. COLLAR ASSEMBLY SUPPLIED SEPARATELY.		
THW-890-2-2	99 -1/2	2527	90-1/8	2289	93	2362	78-1/4	1988	2. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.		
THW-896-2-2	105-1/2	2680	96-1/8	2442	99	2515	84-1/4	2140	3. DRAWING IS NOT TO SCALE.		
THW-8102-2-2	111 -1/2	2832	102-1/8	2594	105	2667	90-1/4	2292	4. ALL DIM'S 1/8 (3) UNLESS OTHERWISE SHOWN.		
THW-8108-2-2	117 -1/2	2985	108-1/8	2646	111	2819	96-1/4	2445	5. DIMENSIONS SHOWN AS: In.(mm)		
THW-8114-2-2	123 -1/2	3137	114-1/8	2899	117	2972	102-1/4	2597	CUSTOMER:		
THW-8120-2-2	129 -1/2	3289	120-1/8	3051	123	3124	108-1/4	2750	LOCATION:		
THW-8126-2-2	135 -1/2	3442	126-1/8	3204	129	3277	114-1/4	2902	ENGINEER :		
THW-8132-2-2	141 -1/2	3594	132-1/8	3356	135	3429	120-1/4	3054	ORDER No.:		
THW-8138-2-2	147 -1/2	3747	138-1/8	3508	141	3581	126-1/4	3207	PROJECT/JOB:		
									LOCATION:		
									TAG:		
									QUOTE #		